



US006351482B1

(12) **United States Patent**
Puzey

(10) **Patent No.:** **US 6,351,482 B1**
(45) **Date of Patent:** **Feb. 26, 2002**

(54) **VARIABLE REFLECTIVITY MIRROR FOR INCREASING AVAILABLE OUTPUT POWER OF A LASER**

(75) **Inventor:** **Kenneth A. Puzey**, Essex Junction, VT (US)

(73) **Assignee:** **Tera Comm Research, Inc.**, Essex Junction, VT (US)

(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** **09/210,931**

(22) **Filed:** **Dec. 15, 1998**

(51) **Int. Cl.⁷** **H01S 3/02; H01S 3/34; H01S 5/183**

(52) **U.S. Cl.** **372/99; 372/46; 372/53; 372/55; 372/92; 372/96**

(58) **Field of Search** **372/99, 92, 96, 372/46, 55, 53**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,295,104	A	10/1981	Burnham	
4,858,240	A	8/1989	Pöhler et al.	372/10
5,015,619	A	5/1991	Wang	505/1
5,036,042	A	7/1991	Hed	350/321
5,110,792	A	5/1992	Nakayama et al.	505/1
5,210,637	A	5/1993	Puzey	359/263
5,323,410	A	6/1994	Masumoto et al.	372/43
5,328,893	A	7/1994	Sun et al.	505/210
5,381,431	A	1/1995	Zayhowski	372/25
5,556,015	A	9/1996	Vincent	224/328
5,568,302	A	10/1996	Puzey	359/157
5,570,386	A	10/1996	Capasso et al.	372/46
5,600,465	A	2/1997	Puzey	359/115
5,768,002	A	7/1998	Puzey	359/245

OTHER PUBLICATIONS

Designers Guide to Fiber Optics; Transmitters and Receivers; "Data Rates and Encoding Formats"; pp. 144-147. (No Date).

L.J. Olafsen et al.; "Near Room Temperature Mid Infrared Interband Cascade Laser"; Applied Physics Letters, vol. 72, No. 19; May 11, 1998.

J. Faist et al., Short Wavelength ($\lambda \sim 3.4 \mu\text{m}$) Quantum Cascade Laser Based on Strained Compensated INGAAS/ALINAS; Applied Physics Letters vol. 72, No. 6, Feb. 9, 1998; pp680-682.

J. Ch. Garcia, et al.; Epitaxially Stacked Lasers with Esaki Junctions; A Bipolar Cascade Laser; Applied Physics Ltrs.; vol 71, No. 26; Dec. 29, 1997; pp. 3752-3754.

B. Levi; Quantum Cascade Laser Makes Progress; Physics Today, vol. 49 8/96, pp. 21.

J. Faist et al.; Quantum Cascade Laser; Science; vol 264, Apr. 22, 1994, pp. 553-556.

C. Gmachl et al.; Continuous-Wave and High-Power Pulsed Operation of Index-Coupled Distributed Feedback Quantum Cascade Laser AT $\lambda \sim 8.5 \mu\text{m}$; Applied Physics Letters; vol. 72, No. 12; Mar. 23, 1998; pp. 1430-1432.

(List continued on next page.)


Primary Examiner—James W. Davie

(74) *Attorney, Agent, or Firm*—Michael Pritzkau; Yoriko Morita

(57) **ABSTRACT**

Output for a laser is greatly increased by altering the transmissivity of a superconductor layer which serves as one of the mirrors of the laser cavity. The superconductor layer is switched between a superconductive state, having reflectivity of one, and a non-superconductive state, having a reflectivity of less than one. When the mirror is in its superconducting state, output power is decreased and power in the cavity is increased, and when the mirror is in its non-superconducting state, output power of the laser is increased and power in the cavity decreases.

42 Claims, 6 Drawing Sheets



US-PAT-NO: 6351482

DOCUMENT-IDENTIFIER: US 6351482 B1

TITLE: Variable reflectivity mirror for
increasing available output power of a laser

----- KWIC -----

Detailed Description Text - DETX (27):

In order for the superconductor to work properly as a mirror the photon energy must not be greater than the band gap of the superconductor. Therefore gain media for low photon energy are particularly useful in the present invention. Such gain media include lead salts and Quantum Cascade structures. Quantum Cascade structures use bandgap engineering techniques to allow common semiconductor materials to emit lower energy photons than were previously possible. Quantum Cascade structures are described in L. J. Olafsen et al. "Near-room-temperature mid-infrared interband cascade laser," Applied Physics Letters, vol. 72, no. 19, May 11, 1998, pages 2370-2372; J. Faist et al. "Short wavelength (λ .about.2.4 microns) quantum cascade laser based on strained compensated InGaAs/AlInAs," Applied Physics Letter, vol. 72, no. 6, Feb. 9, 1998, pages 680-682; and J. Garcia et al. "Epitaxially stacked lasers with Esaki junctions: A bipolar cascade laser," Applied Physics Letters, vol. 71, no. 26, Dec. 29, 1997, pages 3752-3754. An antireflection coating can be deposited on the end-face of a quantum cascade laser using chemical vapor deposition, plasma arc deposition or other commonly practiced methods. Then superconducting mirrors can be used to form an external

Fabry-Perot cavity
around the Quantum cascade gain medium.